

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Delphion

RESEARCH

INTEGRATED IAM

SERVICES

INSIDE DELPHION

My Account | Products | News | Events

Search: Quick/Advanced | Boolean | Advanced

The Delphion Integrated View

Buy Now:  PDF | [More choices...](#)Tools: Add to Work File: [Create new Work File](#) View: [INPADOC](#) | Jump to: [Top](#)  [Email this to a friend](#)

Title: JP2000251890A2: NEGATIVE ELECTRODE FOR NONAQUEOUS ELECTROLYTE SECONDARY BATTERY, AND SECONDARY BATTERY USING THE SAME

Country: JP Japan
Kind: A2 Document Laid open to Public inspection

Inventor: TAJIRI HIROYUKI;
 YADA SHIZUKUNI;
 KIKUTA HARUO;

Assignee: OSAKA GAS CO LTD
[News, Profiles, Stocks and More about this company](#)

Published / Filed: Sept. 14, 2000 / Feb. 26, 1999

Application Number: JP1999000050122

IPC Code: [H01M 4/58](#); [H01M 4/02](#); [H01M 10/40](#); [H01M 4/62](#);

Priority Number: Feb. 26, 1999 JP1999000050122


Abstract: **Problem to be solved:** To provide an electrode of high capacity, capable of easily enhancing a density without crashing an active material particle, prevented from decomposition of an electrolyte to exhibit superior potential smoothness, and provide a secondary battery using the electrode.

Solution: In this negative electrode, a carbon material prepared by mixing at least one kind selected from among a group of artificial graphite and natural graphite, and a carbon material having a volatile component in its surface or its inside, and by firing a mixture provided therein is used as an active material particle, resin is used as a binder, metal is used as a current collecting material, and the electrode has 20-35% of porosity, 1.20-1.60 g/cm³ of electrode density and 400 mAh/cm³ or more of electrode capacity.

COPYRIGHT: (C)2000,JPO

Family: [Show 2 known family members](#)

Other Abstract Info: CHEMABS 133(14)196055D CHEMABS 133(14)196055D DERABS C2000-642218 DERABS C2000-642218



[View Image](#)

1 page



[Nominate](#)

[this for the Gallery...](#)



(19)

(11) Publication number: **2000251890 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **11050122**(51) Intl. Cl.: **H01M 4/58 H01M 4/02 H01M 10/40**(22) Application date: **26.02.99**

(30) Priority:

(43) Date of application
publication: **14.09.00**(84) Designated contracting
states:(71) Applicant: **OSAKA GAS CO LTD**(72) Inventor: **TAJIRI HIROYUKI
YADA SHIZUKUNI
KIKUTA HARUO**

(74) Representative:

**(54) NEGATIVE ELECTRODE
FOR NONAQUEOUS
ELECTROLYTE
SECONDARY BATTERY,
AND SECONDARY BATTERY
USING THE SAME**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide an electrode of high capacity, capable of easily enhancing a density without crashing an active material particle, prevented from decomposition of an electrolyte to exhibit superior potential smoothness, and provide a secondary battery using the electrode.

SOLUTION: In this negative electrode, a carbon material prepared by mixing at least one kind selected from among a group of artificial graphite and natural graphite, and a carbon material having a volatile component in its surface or its inside, and by firing a mixture provided therein is used as an active material particle, resin is used as a binder, metal is used as a current collecting material, and the electrode has 20-35% of porosity, 1.20-1.60 g/cm³ of electrode

density and 400 mAh/cm³ or more of
electrode capacity.

COPYRIGHT: (C)2000,JPO